

Wood Flooring



Primatech G100

Hot Melt Glue APPLICATOR for Hardwood Flooring and many other applications



STARTER ROWS – T-MOLDING – HOLLOW SPOT REPAIR – BOARD REPLACEMENT
– BASEBOARD ¼ ROUND – TRIMS & TRANSITIONS – **and more**


- Adjustable temperature 284° F to 428° F
 - Powerful 220Watt heating element
 - Fast activation – Ready in 5 minutes
- Stroke adjustment for precise, consistent dispensing
- Standard nozzle & Spot repair nozzle
 - No downtime on jobsite
 - Secure Start and Finish rows
 - Labor and material savings

PrimStick® Hot Melt Adhesive

- Green friendly, no toxins
- Quick as a Wink curing time
- Heat resistance & Cold flexibility
- Smooth and easy application
- Does not harden or brittle (cabinet making)
 - No VOC's, no Fumes, no Waste
 - Some other applications : building maintenance, tile repair, etc.

Holds fast on any concrete or wood subfloors

WOOD – CONCRETE - PAPER – GLASS – CERAMICS – METAL –
MELAMINE – ABS – RUBBER - PVC – MDF – **and more**



PrimStick	Working / cure time	Bag	Bag/case	Tool
G060 (½" x 10" glue stick)	60 seconds / 5 minutes	1 lb	22	G100
G180 (½" x 10" glue stick)	180 seconds / 8 minutes	1 lb	22	G100

Printed in Canada 07-2013

Primatech inc.
1135, rue Jérémie-Fortin
Québec QC Canada G1J 1R8

Genuine & Authentic
Primatech®

DECADES OF
INNOVATIONS

USA / CAN 1(800) 363-1962 sales@primatech.ca